



FloorAmerica Products
2200 Dortch Avenue
Nashville, TN 37210
615-256-5723

Product Data Code	F-75
Revision #:	11-1
Date:	01/01/2011

FloorStrip-1

Product Data Sheet

PHYSICAL FEATURES

- Physical Form: Liquid
- Color: Clear; darkens over time
- Odor: Sweet ether-like odor
- Evaporation Rate: <300 mmHg @ 20° C
- Flash Point: None to boiling
- Boiling Point: 104° F
- Weight: 9.6 – 9.9 pounds per gallon
- pH: 10 - 11

KEY BENEFITS

- FloorStrip-1 allows the removal of a coating without mechanical shot-blasting or scarifying so no damage is done to the concrete. Perfect for the use of Acid Stains.
- Can be used to breakdown a coating before a shot-blasted is used to minimize the hit of the shot
- Apply and allow drying over night and eliminating liquid waste.

Product Highlights

FloorStrip-1 is a methylene chloride based coating remover for concrete floors. Once applied you will notice the product start blistering most coatings within minutes and some time even faster.

- Best results when used at 68 – 72 degrees F [product temperature is 20 degrees cooler than ambient temperature]
- Apply at 100 to 200 feet per gallon and allow dwell time.
- May have to be reapplied for thicker coatings, it will only break through 5 to 8 Mils per application.
- Scrappers can be used to remove coating before next application.
- Once removed, use FloorScrub-2 detergent to scrub and neutralize the surface then rinse with fresh water.

Disposal Information

Sludge and rinse waters should be evaluated according to the stripped finish it contains and be disposed accordingly.

Some Finish residues may not be discharged to local wastewater treatment plants. **Provide MSDS and finish residue information to local water treatment authorities prior to initial discharge.**

Local regulations will vary and many do not allow rinse water discharge. **Never** dispose directly to water bodies such as streams or ponds, to septic tanks, or directly onto the ground. Submit MSDS to your hazardous waste disposal company for proper hazardous waste profile.



FloorAmerica Products
2200 Dortch Avenue
Nashville, TN 37210
615-256-5723

Product Data Code	F-75
Revision #:	11-1
Date:	01/01/2011

RELATED PRODUCTS

Our other products that work hand in hand with FloorStrip-1 for a total Chemical Surface Preparation

- Clean with FloorScrub 1 or 2
- Etch with FloorEtch-1
- Nano Etch with Fluor-Gen

ADDITIONAL INFORMATION

More information can be found at: www.FloorAmerica.com

Or e-mail us at order@FloorAmerica.com

FloorAmerica Products
2200 Dortch Avenue
Nashville, TN 37210-4906

615-256-5723 Office
615-254-9272 Fax

Hours – Central Time Zone
7:00 AM to 3:00 PM
Monday - Friday

Safety Information

FloorStrip-1 contains methylene chloride which has been shown to cause cancer in certain laboratory animals. OSHA has set a permissible exposure level of 25 ppm for methylene chloride. Use proper ventilation and if necessary supplied air respirator, air-purifying cartridge respirators are unacceptable for use with methylene chloride. Excessive vapors can cause dizziness, nausea, headaches and asphyxiation. Product may burn skin on contact. See MSDS for other acute and chronic hazards.

Always wear chemical resistant gloves, proper eye protection, and adequate ventilation when using any chemical product.

Technical Specifications

- Harmful – Stow away from foodstuffs
- Store in a cool shaded area. This material develops unsafe pressure when stored in sunny or very hot areas.
- WARNING Open Container Slowly
- Stir product well before using.
- This Product is for Professional Use Only
- Do Not Use Until You Have Read MSDS

Packaging Information			
Product	Container Size	Code	Weight
FloorStrip-1	5 Gallon Pail	F-75-5	55 lb
FloorStrip-1	55 Gallon Drum	F-75-55	580 lb

This document is copyright © January 01, 2011 FloorAmerica Products Nashville, Tennessee 37210. All rights reserved. This document is provided for information purposes only; contents are subject to change without notice. It is not warranted to be error-free, nor subject to any other warranties or conditions including implied warranties and conditions of merchantability or fitness for a particular purpose.