

FloorAmerica

Epoxy Flooring Chemicals & Supplies

2200 Dortch Avenue
Nashville, TN 37210
Voice.615.256.5723 Fax.615.254.9272
www.FloorAmerica.com

PRODUCT DATA

For more information, contact:
Customer Service 615-726-0884
All prices are subject to change

FloorGrit

Description

This product is a texture that can be mixed directly into any epoxy or urethane system. When rolled out at a spread rate of 250 to 450 square feet per gallon makes a very even texture.

Applications

FloorGrit can be added directly into the resin as mixed. It will stay suspended in the product until rolled onto the floor. It can be used in epoxy, urethanes, paints or any other resinous coating. Should the product set for any length of time it should be re-stirred every 5 minutes. Helps take out imperfections on any quartz's system. Just add in the topcoat for that perfect looking floor. Also apply using our flat squeegee and then back roll. Squeegee # 6118, 6124, 6130, 6136

Specifications

FloorGrit is a grounded clear acrylic plastic material. Just add 10-16 ounces into a 1.5-gallon mix of epoxy or urethane and roll out at 250 to 450 feet per gallon. Remember the thicker the resin is applied the less grit will show. Best if used in the topcoat at the above spread rate. Use a 3/8" nap roller for back roll. FloorGrit come in a re-useable easy open Life-Latch Pail.

Pricing

Part #	Product & Grit	Size	Net Weight	Price
SM-104	FloorGrit – Medium	2 gal Bucket	10 lb.	\$40.00
SM-105	FloorGrit – Medium	5 gal Bucket	25 lb.	\$95.00
SM-106	FloorGrit - Medium	Drum	100 lb.	\$265.00
	FloorGrit - Fine	2 gal Bucket	9 lb.	\$35.00
	FloorGrit - Fine	5 gal Bucket	25 lb.	\$90.00
	FloorGrit - Fine	Drum	100 lb.	\$265.00